


Propscreen is a simple and cost effective, temporary floor-to-ceiling poles and polythene solution. Offering quick installation for internal segregation and dust containment during; fit out, renovation and maintenance work.



Cost effective




Quick to install



No fixing required



Next day delivery



Prevent dust and overspray

## FEATURES & BENEFITS

FEATURES	BENEFITS
Light weight material	<ul style="list-style-type: none"> <li>• Easy to install and move around site</li> </ul>
Floor-to-ceiling pole clamp	<ul style="list-style-type: none"> <li>• Creates dust tight and overspray containment environment</li> </ul>
Easy install zip-door	<ul style="list-style-type: none"> <li>• For easy access whilst creating a dust tight seal</li> </ul>
Fire rated material	<ul style="list-style-type: none"> <li>• Adheres to and is registered to LPCB standards</li> </ul>
Quick and clean to install	<ul style="list-style-type: none"> <li>• Get set up quickly without skilled labour</li> <li>• Reduce down time to project start</li> <li>• React quickly to maintenance requirements</li> </ul>
Pole extension between 1.9m and 6m (1.9-3.5m, 2.7-4.5m and 3.2-6m)	<ul style="list-style-type: none"> <li>• Works across multiple environments</li> </ul>
No fixing required	<ul style="list-style-type: none"> <li>• No damage to existing building or decoration</li> <li>• Easily reconfigure, remove or relocate without damage</li> </ul>
Large UK stock	<ul style="list-style-type: none"> <li>• Gets dispatched quickly; as standard next business day delivery</li> </ul>



Propscreen is installed using easy to adjust poles, which can extend between 1.9 and 6m high and the polyethene sheets are supplied in 4m (w) x 50m (l) rolls, with no fixing required.



## TECHNICAL SPECIFICATIONS

Material composite	Low Density Polyethylene based Polyethylene film
Material thickness	125mu
Length and width of polythene sheet	25m or 50m x 4m
Pole length and extension	1.9-3.5m, 2.7-4.5m and 3.2-6m
Material fire rating examples	LPS1207

## TECHNICAL SPECIFICATIONS



Poles can be extended up to 6 metres using a simple push and click locking system



Polythene sheets are tensioned and secured using floor-to-ceiling poles

WE HAVE CREATED CUSTOMISED SOLUTIONS FOR MANY INCLUDING...



This fact sheet is for illustrative purposes only and based on the latest information at the time of print. Installation methods may vary depending on specific project requirements. Westgate reserve the right to make changes at any time without notice.

westgateuk.co.uk +44 (0)1785 242181 salesteam@westgateuk.co.uk