



INTEGRATED ROLLER AND FOLD DOORS



Fastflex roller and fold fast-action doors can be used internally or externally, supplied standalone or as part of your partitioning project.

Fastflex fast action doors provide customers with managed and optimised traffic flow, temperature control, ingress control and reduced energy consumption.

We offer a range of doors for factory and warehouse environments all of which come with a variety of fabric, size, operation and safety options, allowing our customers to choose a door that best works for them.



Key features



Highest quality parts guarantee reliability



Factory assembly & testing minimises installation times



Can form part of an integrated solution



Range of fabric & size options



Replacement parts available quickly



Temperature, dust and ingress control

Typical uses include;

- Create airlocks for temperature, dust and ingress control
- Internal doors for segregation of different operational areas i.e. production and storage areas
- External doors
- Can be designed and installed as part of a Flexiwall installation

Benefits

- Door assembly includes quality GFA drive train and control gear (unless specified otherwise) to reduce breakdowns and failures
- Doors pre-assembled and tested before leaving the factory for quick and seamless installation
- Anti-crash system self-repairs to reduce operational downtime in the event of impact
- Bespoke sizes available, up to 15m wide
- Range of operation options including radar, photo cell and push button
- Safety light curtain up to 2.5m from floor
- A range of solutions to suit your business needs; choose from Thermal, Acoustic, Antistatic, Hermetic and Food Industry Approved solutions
- Range of fabrics and vision panel options
- Wind loads; doors achieve Wind Class 2 as standard. Solutions available on request to deliver Wind Class 4.
- National certified installation service
- Repair and maintenance service

Technical data

Max door size internal:	9m(w) x 7m(h) (fold door) 5m(w) x 5(m) (roller door)
Max door size external:	6m(w) x 6m(h) (fold door) 5m(w) x 5(m) (roller door)
Opening speeds:	up to 2.5 m/s (roller door)
Closing speeds:	up to 0.8 m/s (Internal) up to 0.8 m/s (External)
Safety bottom edge protection:	yes
Safety light curtain:	yes (up to 2.5m)
Self-repairing zip edge:	roller door only
Materials:	Frame: Galvanized (EN 10346:2009) or powder coated steel guide rails, curtain hood and motor cover (316 grade stainless steel option)
Electricity supply:	Single phase or 3 phase (depending on door size)



WE HAVE CREATED SOLUTIONS FOR MANY INCLUDING...



CALL US TODAY ON +44 (0)1785 242181 AND BOOK A NO OBLIGATION SITE SURVEY WITH ONE OF OUR SECTOR SPECIALISTS...

Could Fastflex work for you? Find out more at westgateuk.co.uk/fastflex